

H series gas engines and gen-sets biogas

1,200/1,500/1,800 rpm



G-24HM & G-42HM

Engine Parameters ²⁾	English Units	Metric Units	G-24HM				G-42HM			
			1,500		1,800		1,500		1,800	
Speed	rpm									
Engine power	bhp	kWb	697	(520)	697	(520)	1,395	(1,040)	1,395	(1,040)
Cylinder arrangement			in Line 8				V12			
Mean effective pressure	psi	bar	252	(17.4)	210	(14.5)	286	(19.7)	238	(16.4)
Bore	inch	mm	5.98	(152)	5.98	(152)	6.30	(160)	6.30	(160)
Stroke	inch	mm	6.50	(165)	6.50	(165)	6.89	(175)	6.89	(175)
Displacement	cu.in	Litres	1,460	(24.0)	1,460	(24.0)	1,718	(42.2)	1,718	(42.2)
Mean piston speed	in/s	m/s	325	(8.3)	390	(9.9)	344	(8.8)	413	(10.5)
Compression ratio			11.8:1				11.9:1			
Combustion air massflow	lbs/hr	kg/h	4,211	(1,910)	5,247	(2,380)	10,119	(4,590)	10,251	(4,650)
Packaged ventilation air flow ³⁾	scfm	m ³ /h	21,424	(36,400)	21,424	(36,400)	42,849	(72,800)	42,849	(72,800)
Engine coolant capacity (Main circuit) ⁴⁾	gal.	Litres	21	(80)	21	(80)	63	(240)	63	(240)
Engine coolant capacity (Aux. circuit) ⁴⁾	gal.	Litres	5	(20)	5	(20)	20	(75)	20	(75)
Lube oil capacity ⁵⁾	gal.	Litres	45	(169)	45	(169)	107	(403)	107	(403)
Lube oil consumption ⁵⁾	lbs/bhp.hr	g/kWh	0.00058	(0.35)	0.00058	(0.35)	0.00025	(0.15)	0.00025	(0.15)

G-24HM & G-42HM

Energy Balance	English Units	Metric Units	G-24HM		G-42HM					
Generator efficiency ^{6) 7)}	%	%	96.4	96.2	97.2	96.7				
Electrical power ^{6) 7)}	kWe	kW	501	500	1,011	1,006				
Jacket (HT) water heat (oil cooler included)*	Btu x 1,000/hr	kW	788.7	(231)	679.5	(199)	1,864.3	(546)	1,959.9	(574)
Intercooler (LT) water heat	Btu x 1,000/hr	kW	273.2	(80)	327.8	(199)	198.0	(58)	194.6	(57)
Exhaust heat - cooled to 120°C	Btu x 1,000/hr	kW	874.1	(256)	1055.1	(309)	1,697.0	(497)	1,908.7	(559)
Engine radiation heat	Btu x 1,000/hr	kW	99.0	(29)	136.6	(40)	239.0	(70)	239.0	(70)
Generator radiation heat	Btu x 1,000/hr	kW	63.9	(19)	67.5	(20)	99.4	(29)	117.2	(32)
Fuel consumption ⁸⁾	Btu x 1,000/hr	kW	4,029.0	(1,180)	4,244.1	(1,243)	8,071.7	(2,364)	8,382.4	(2,455)
Mechanical efficiency		%	44.1		41.8		44.0		42.4	
Electrical efficiency		%	42.5		40.2		42.8		41.0	
Thermal efficiency		%	48.1		48.6		46.6		48.5	
Total efficiency		%	90.5		88.8		89.3		89.4	

G-24HM & G-42HM

System Parameters	English Units	Metric Units	G-24HM				G-42HM			
Jacket (HT) water temperature max.	°F	°C	194	(90)	194	(90)	194	(90)	194	(90)
Jacket (HT) water flow rate min.	gpm	m³/h	141	(32)	123	(28)	167	(38)	167	(38)
Jacket (HT) water flow rate max.	gpm	m³/h	264	(60)	264	(60)	308	(70)	308	(70)
Intercooler stages		Single						Double		
Intercooler (LT) coolant temperature	°F	°C	131	(55)	131	(55)	131	(55)	131	(55)
Intercooler (LT) coolant flow rate min./max.	gpm	m³/h	88	(20)	110	(25)	88	(20)	110	(25)
Intercooler (LT) coolant flow rate min./max.	gpm	m³/h	132	(30)	132	(30)	132	(30)	132	(30)
Exhaust manifold type					Dry					
Exhaust temperature	°F	°C	927	(497)	916	(491)	806	(430)	865	(463)
Exhaust mass flow wet	lbs/hr	kg/h	4,674	(2,120)	5,732	(2,600)	11,067	(5,020)	11,244	(5,100)
Exhaust backpressure max.	psi	mbar	0.65	(45)	0.65	(45)	0.65	(45)	0.65	(45)
Maximum pressure loss in front of air cleaner	psi	mbar	0.073	(5)	0.073	(5)	0.073	(5)	0.073	(5)
Fuel pressure range	psi.	mbar	0.73 - 3.48 (50 - 240)				0.73 - 3.48 (50 - 240)			
Starter battery 2x12 V, capacity required		Ampere-hour	280				280			
Emissions ⁹⁾	English Units	Metric Units	G-24HM				G-42HM			
NOx		g/bhp.hr	< 1.1		< 1		< 1.1		< 1	
CO		g/bhp.hr	< 2.4		< 2.4		< 2.2		< 2.2	
THC (in C1base)		g/bhp.hr	< 4.3		< 4.3		< 4.3		< 4.3	
NMHC (in C1 base)		g/bhp.hr	< 0.7		< 0.7		< 0.7		< 0.7	

1) Reference gas (CH4: 67%, CO2: 33%). For other biogas qualities consult Guascor Energy.

2) Engine performance data acc. to ISO 3046/1 for performance on alternate gases consult Guascor Energy

3) Assumes intake air flow at delta T = 5°C including combustion air

4) Not including pipes and heat exchangers

5) Mean lube oil consumption between maintenance steps

6) At 50 Hz, U = 0.4 kV, power factor = 1

7) At 60 Hz, U = 0.48 kV, power factor = 1

8) With a tolerance of + 5 %

9) Lower emission engines are available; consult Guascor Energy for performance data

G-56HM

Engine Parameters ²⁾	English Units	Metric Units	G-56HM						
			rpm		1,200		1,500		1,800
Speed									
Engine power	bhp	kWb	1,395	(1,040)	1,840	(1,373)	1,810	(1,350)	
Cylinder arrangement			V16						
Mean effective pressure	psi	bar	268	(18.5)	284	(19.6)	232	(16.0)	
Bore	inch	mm	6.30	(160)	6.30	(160)	6.30	(160)	
Stroke	inch	mm	6.89	(175)	6.89	(175)	6.89	(175)	
Displacement	cu.in	Litres	3,436	(56.3)	3,436	(56.3)	3,436	(56.3)	
Mean piston speed	in/s	m/s	276	(7.0)	344	(8.8)	413	(10.5)	
Compression ratio			11.9 : 1						
Combustion air massflow	lbs/hr	kg/h	10,406	(4,720)	13,360	(6060)	13,338	(6,050)	
Packaged ventilation air flow ³⁾	scfm	m ³ /h	42,849	(72,800)	55,621	(94,500)	55,621	(94,500)	
Engine coolant capacity (Main circuit) ⁴⁾	gal.	Litres	69	(260)	69	(260)	69	(260)	
Engine coolant capacity (Aux. circuit) ⁴⁾	gal.	Litres	20	(75)	20	(75)	20	(75)	
Lube oil capacity ⁵⁾	gal.	Litres	111	(419)	111	(419)	111	(419)	
Lube oil consumption ⁵⁾	lbs/bhp.hr	g/kWh	0.00025	(0.15)	0.00025	(0.15)	0.00025	(0.15)	

G-56HM

Energy Balance	English Units	Metric Units	G-56HM					
Generator efficiency ^{6) 7)}	%	%	96.8		97.3		96.9	
Electrical power ^{6) 7)}	kWe	kW	1,007		1,337		1,308	
Jacket (HT) water heat	Btu x 1,000/hr	kW	2,000.9	(586)	2,414	(707)	2,475.5	(725)
Intercooler (LT) water heat	Btu x 1,000/hr	kW	204.9	(60)	276	(81)	290.2	(85)
Exhaust heat - cooled to 120°C	Btu x 1,000/hr	kW	1,659.4	(486)	2,181	(639)	2,516.4	(737)
Engine radiation heat	Btu x 1,000/hr	kW	225.4	(66)	307	(90)	286.8	(84)
Generator radiation heat	Btu x 1,000/hr	kW	99.4	(29)	119.8	(35)	147.5	(43)
Fuel consumption ⁸⁾	Btu x 1,000/hr	kW	8,174.1	(2,394)	10,557	(3,092)	10,868.1	(3,183)
Mechanical efficiency		%	43.4		44.4		42.4	
Electrical efficiency		%	42.2		43.2		41.1	
Thermal efficiency		%	47.3		46.1		48.6	
Total efficiency		%	89.5		89.3		89.7	

G-56HM

System Parameters	English Units	Metric Units	G-56HM					
Jacket (HT) water temperature max.	°F	°C	194	(90)	194	(90)	194	(90)
Jacket (HT) water flow rate min.	gpm	m ³ /h	181	(70)	220	(50)	220	(50)
Jacket (HT) water flow rate max.	gpm	m ³ /h	308	(70)	308	(70)	308	(70)
Intercooler stages			Double					
Intercooler (LT) coolant temperature	°F	°C	131	(55)	131	(55)	131	(55)
Intercooler (LT) coolant flow rate min.	gpm	m ³ /h	66	(15)	88	(20)	110	(25)
Intercooler (LT) coolant flow rate max.	gpm	m ³ /h	132	(30)	132	(30)	132	(30)
Exhaust manifold type			Dry					
Exhaust temperature	°F	°C	763	(406)	766	(408)	878	(470)
Exhaust mass flow wet	lbs/hr	kg/h	11,222	(5,090)	13,250	(6,010)	14,462	(6,560)
Exhaust backpressure max.	psi	mbar	0.65	(45)	0.65	(45)	0.65	(45)
Maximum pressure loss in front of air cleaner	psi	mbar	0.073	(5)	0.073	(5)	0.073	(5)
Fuel pressure range	psi	mbar	0.73 - 3.48 (50 - 240)					
Starter battery 2x12 V, capacity required	Ampere-hour		280					
Emissions ⁹⁾	English Units	Metric Units	G-56HM					
NOx	g/bhp.hr		< 1		< 1.1		< 1	
CO	g/bhp.hr		< 2.2		< 2.2		< 2.2	
THC (in C1base)	g/bhp.hr		< 4.3		< 4.3		< 4.3	
NMHC (in C1 base)	g/bhp.hr		< 0.7		< 0.7		< 0.7	

Heat included in with the jacket water heat

- Fuel blending system available on request

- The values given in this data sheet are for information purposes only and not binding

CO: 1,200/1,500/1,800 rpm

Generator frequency: 50/60 Hz

Applicable gas types: Biogas.

Dimensions and other data

Engine Dimensions	English Units	Metric Units	G-24HM		G-42HM		G-56HM	
Width	in.	mm	81.8	(2,079)	84.2	(2,141)	70.3	(1,787)
Length	in.	mm	126.9	(3,223)	159.1	(4,041)	134.2	(3,409)
Height	in.	mm	62.6	(1,590)	87.3	(2,217)	85.2	(2,165)
Dry weight	lb	kg	9,259	(4,200)	16,535	(7,500)	16.5	(7,500)

Engine Dimensions	English Units	Metric Units	G-24HM		G-42HM		G-56HM	
Width	in.	mm	81.8	(2,079)	84.8	(2,155)	84.2	(2,141)
Length	in.	mm	155.5	(3,952)	191.5	(4,865)	218.3	(5,545)
Height	in.	mm	68.4	(1,738)	93.4	(2,373)	91.3	(2,319)
Dry weight	lb	kg	13,735	(6,230)	23,667	(10,735)	26,896	(12,200)

Noise emissions*

Engine Noise dB(A)	HZ (Frec. Band)	G-24HM		G-42HM		G-56HM		
	-	1,500	1,800	1,500	1,800	1,200	1,500	1,800
	125	73	67	71	-	71	73	70
	250	83	77	81	74	77	83	84
	500	85	80	84	88	79	85	82
	1,000	88	88	87	83	81	88	86
	2,000	92	91	90	90	88	92	92
	4,000	89	87	89	87	83	89	88
	LpA, å dB(A)	96	94	94	94	90	96	95

Dimensions and other data

Noise emissions*

Exhaust Noise dB(A)	HZ	G-24HM		G-42HM		G-56HM		
		63	100	102	105	106	99	102
125	121	131	119	129	109	122	125	
250	129	133	129	133	115	128	136	
500	116	122	116	123	116	122	127	
1,000	116	119	115	117	114	119	121	
2,000	115	117	113	114	114	117	117	
4,000	112	110	111	111	116	112	113	
LpA, a dB(A)	130	136	130	135	122	130	137	

Notes: Data obtained according to ISO 9614-2 • Data obtained @ 1 m from engine according to UNE-EN ISO-11203:1996
Maximum data standard deviations = ± 4 dB(A)

Published by
Guascor Energy

Oikia, 44
20759 Zumaia (Gipuzkoa) Spain
POBox 30
Tel: (Int'l +34) 943 86 52 00
Fax: (Int'l +34) 943 86 52 10

www.guascorenergy.com

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

© Guascor Energy 2022

Guascor Energy is a trademark licensed by Guascor Energy

